



**UNIVERSITY OF CALICUT
CALICUT UNIVERSITY INSTITUTE OF ENGINEERING AND TECHNOLOGY**

No:41173/CUIET-A-ASST-1/2013/CU

Date:05.10.2015

TENDER NOTICE

Sealed Competitive tenders are invited for the supply of Lab items as per the list attached to the
EEE Department of CUIET.


Tender forms can be downloaded from the University website www.universityofcalicut.info .

Cost of tender form :- 0.2% of the cost of tender rounded to the nearest multiple of 100,subject to a
minimum of Rs. 400/- and maximum Rs.1500/- + VAT as applicable.

EMD :- 1% of the quoted rate subject to a minimum of Rs.1,500/- drawn in favor of Finance Officer ,
University of Calicut.

The rates quoted should be inclusive of all taxes,installation charges,service guaranty of a
minimum of one year and transportation etc.

The quotations should reach the undersigned on or before 26.10.2015


Dr. Rahmathunza I.

Principal

Principal
Calicut University
Institute of Engineering & Technology
Thenhipalam. P.O., Malappuram - 673 626

EEE Department

Power Electronics Lab :-

Sl. No	Item name	Specification	No of Units required
1	CRO	Cathode-Ray Oscilloscope 25MHz , 2 channel, 4 trace with microcontroller based, Note: demonstration if necessary	1
2	Digital storage oscilloscope	<u>Digital Storage Oscilloscope</u> 50 MHz digital storage oscilloscope with differential probe dual channel; color, real time sampling:1GSa/s,memory:1 M Points, Display analog along with USB & RS232 Port &software, alternate trigger, circuit test facility, read and write USB memory, harmonic analysis	2
3	Analog Meter	Voltmeter (0-30) MC	4
4		Voltmeter (0-30) MI	4
5		Ammeter (0-10) mA MC	4
6		Ammeter (0-10)mA MI	4
7		Analog multimeter	6
8		<u>Center trapped Transformer</u> 230V/(12-0-12),2A,Heavy Duty	4
9	3-phase IGBT based inverter stack(Rectifier +inverter+chopper) including PWM Card+Power supply	<u>3-phase IGBT based inverter stack(Rectifier+inverter+chopper) including PWM Card+Power supply</u> <u>Suggested Experiments</u> <u>1.To control the output of the IGBT based inverter using PWM technique</u>	1

10	Trainer kit for characteristic s of SCR (Aim: To plot static & dynamic characteristic s of SCR)	<u>SCR CHARACTERISTICS STUDY</u> <u>TRAINER</u> * Basic static characteristics study trainer. * Variable DC power supply (<u>Suitable value</u>) for SCR V_{ak}. * Variable DC power supply (<u>Suitable value</u>) for gate voltage of all devices. * Separate section for SCR characteristics. * Two No's fixed load resistor for all devices. * Four No's potentiometer to vary all voltages. * LED indication for all power supply. * Three No's. Digital multimeter for measurement of device parameters. * 230V AC input with Power ON/OFF switch. * Necessary test points are terminated at sockets so that the student can monitor / measure / study the signals using CRO, DVM, etc., SUGGESTED EXPERIMENTS : 1. To plot static characteristics of SCR * Necessary test points are terminated at sockets so that the student can monitor / measure / study the signals using CRO, DVM, etc., Note: demonstration if necessary	1
11	Trainer kit for dynamic characteristic s of SCR	<u>TRANSIENT CHARACTERISTICS OF SCR</u> - a). Transient Characteristics of SCR : * One SCR with proper heat sink * Turn-ON transient (OR) turn off transient characteristics can be studied. * IC Based square wave generation for V_{AK} and V_{GK} * One No. of fixed load resistor. - b). Power Supply : * 230V AC Input, $\pm$ <u>Suitable value</u> V DC for control circuit * Power ON/OFF switches with indication. * Necessary test points are terminated at sockets so that the student can monitor / measure / study the signals using CRO, DVM, etc., SUGGESTED EXPERIMENTS : 1. To plot dynamic characteristics of SCR	1

12	1. Trainer kit for phase control using R, RC and UJT Trigger circuit with Single phase controlled rectifier	<u>UJT, R, R-C CIRCUITS TRIGGERING FIRING MODULE</u> * Consists of three types of basic firing circuit to trigger SCR. * Separate sections for R - firing, RC - firing, UJT firing circuit. * <u>Suitable value</u> [V AC / AMP] provided for firing circuit input voltage. * One potentiometer used to vary the firing angle of UJT firing circuit. * One potentiometer used to vary the firing angle of R - firing circuit. * One potentiometer used to vary the firing angle of RC - firing circuit. * One no. toggle switch for ON/OFF <u>Suitable value</u> VAC. * Four No's firing pulses terminated on the front panel for connecting external device module. (UJT firing circuit) * 1:1:1 Pulse transformer used for UJT firing circuit pulse isolation. * One no. SCR with snubber circuit forms half wave controlled converter circuit for checking all three firing circuit. * 230V, 50HZ AC input, fuse provided for over load protection. * One no. rocker switch with LED Indication for power ON/OFF. * Necessary test points are terminated at sockets so that the student can monitor / measure / study the signals using CRO, DVM, etc., <u>SUGGESTED EXPERIMENTS :</u> 1. Study of UJT firing circuit. 2. Obtain the load voltage waveform for UJT Trigger circuit with Single phase controlled rectifier 3. Single phase half wave controlled converter using R - firing. 4. Single phase half wave controlled converter using RC - firing. 5. Analysis of load voltage for different firing angles for Rand RC firing	1
----	---	--	---

13	Trainer kit for AC Voltage Controller using TRIAC	<u>AC PHASE CONTROL USING SCR</u> This trainer module consists of two separate section a. UJT based firing circuit for SCR AC Regulator b. DIAC , R & C based firing circuit for TRIAC AC Regulator UJT based firing circuit for SCR AC Regulator : <u>Suitable value</u> V AC for UJT firing circuit (<u>Suitable value</u> AC obtained through 230/ <u>Suitable value</u> V AC, A step down transformer) *One potentiometer is used to vary the firing angle *Two isolated pulses for SCR *Isolation obtained by pulse isolation transformer *Two no. of SCR with heat sink (600V,12A) provided for power circuit *Power circuit input volt 0-230V AC (External) *fan load b. DIAC based firing circuit for TRIAC AC Regulator DIAC firing for TRIAC * One TRIAC with heat sink (600V/12A) *230V operation *One lamp load or fan(Optional) *One potentiometer is used to vary the firing angle Output voltage 0- 230V AC * Necessary test points are terminated at sockets so that the student can monitor / measure / study the signals using CRO, DVM, etc., SUGGESTED EXPERIMENTS : 1. speed control of fan using TRIAC	1
----	---	--	---

14	Trainer kit for Single Phase fully controlled SCR Bridge circuit	<u>SINGLE PHASE SCR BRIDGE CONVERTER</u> * Consists of firing circuit, SCR power circuit and load. * Line synchronized IC based linear firing circuit. * Line synchronization achieved by step - down transformer. * Four no. firing pulses to trigger four SCRs. * 1:1:1 Pulse transformer used for pulse isolation. • * One No. Potentiometer used to vary the firing angle ($180^\circ - 0^\circ$). * Carrier logic implemented carrier frequency KHz. * One no. toggle switch with debouncing logic for pulse ON/OFF. * Provision to control the firing angle through external [Any value]. * Power circuit consists of four no. SCR with fuse protection. * Anode, Cathode, Gate terminals are terminated in the front panel for user connection. * Necessary test points are terminated at sockets so that the student can monitor / measure / study the signals using CRO, DVM, etc., * Suitable value [V AC, AMP] provided for power circuit input with ON/OFF switch. * One no. fixed R, L load provided. * 230V, 50Hz AC input with ON/OFF rocker switch, fuse for over load. * Necessary test points are terminated at sockets so that the student can monitor / measure / study the signals using CRO, DVM, etc., SUGGESTED EXPERIMENTS : 1. Single phase fully controlled converter with R and R - L load. 2. Study the operation of single phase fully converter with RL load & with & without freewheeling diode Note: 1.demonstration if necessary 2.povision to connect and disconnect freewheeling diode	1
----	--	---	---

15	Trainer kit for Single-phase half bridge/full bridge inverter using power MOSFET/IGBT	Single-phase half bridge/full bridge inverter using power MOSFET/IGBT Aim: Design and set up a single phase half-bridge/full-bridge inverter and observe the waveforms across load and firing pulses. * Necessary test points are terminated at sockets so that the student can monitor / measure / study the signals using CRO, DVM, etc., SUGGESTED EXPERIMENTS : 1. To control the output of the IGBT based inverter using PWM technique	1
16	Trainer kit for Step down Chopper using MOSFET	Step down Chopper using MOSFET * One number of powers MOSFET used as power switch with suitable heat sink. * IC based PWM generator. * One number of high speed Opto isolator provided for PWM isolation. * Driver IC used to drive power switch. * High frequency transformer provided for isolation. * Power circuit I/P voltage: <u>Suitable value</u> (DC). * Output voltage: <u>Suitable value</u> [VDC/ amp]. 230V AC input, <u>Suitable value</u> DC for control circuit. * One number of fuse provided for protection. * Voltage feed back from the output for closed loop operation. * One no. of Potentiometer used for PWM variation * L & C provided for filters * Necessary test points are terminated at sockets so that the student can monitor / measure / study the signals using CRO, DVM, etc., SUGGESTED EXPERIMENTS : 1. To obtain the output voltage waveform for resistive load	1

Advanced Electrical Lab:-

Sl. No	Item name	Specification	No of Units required
1	Signal Generator	a)Frequency range -0 to 2 Mhz b)Frequency resolution -.001 hz c)Frequency error -<10 ⁻⁷ d)Power output—120 dbm to +10dbm or better e)Resolution -0.1db f)Types of modulation –AM,FM,Phase modulation,Pulse modulation g)Interface –IEEE 488,EthernetPort,USB	2

2	Trainer kit for Experiment using PLC	PROGRAMMABLE LOGIC CONTROLLER TRAINER WITH DEMONSTRATOR : This trainer is based on Siemens make PLC It consist of, a) Micro PLC b) Programming Software, c) Communication cable d) Demonstration panel consist of SPDT switches, as digital inputs LED Lamps to simulate digital outputs, software to program in ladder language. e) PLC Specifications * Digital inputs (24V DC) * Data memory 12KB, Program memory 12KB * 0.22 Msec bit operating speed * 256 Timers, Counters. * Built in real time clock * 24V DC power supply for operating voltage * RS485 Communication interface * 6 High speed counter with 30 KHz * 2 PWM outputs with 20 KHz * 2 PWM outputs with 20 KHz * 2 PWM outputs with 20 KHz - f). 32 bit floating point for Arithmetic operation - Demonstration Panel g) 14 SPDT Switches provided to simulate to the digital inputs h) 10 LED Lamps provided with fuse protection to simulate the digital outputs i) One 24 V DC source provided for panel utility. j) 2 Channel PWM (or) HSC connecting facility k) All the components are mounted in attractive powder coated metal frame l) All inputs are terminated on the frontpanel on socket type connector for inter connecting of application. Programming Software : Windows based Powerful software provided to write program in ladder languages. Siemens PLC programming software. # Step7 200. # IEC 6113 standard m) Interface Cable A special point to point interface cable provided for communication. Note: demonstration if necessary	1
---	--------------------------------------	--	---

3	8086	8086/8088 MICROPROCESSOR TRAINER KIT Processor: * Intel 8086/8088 CPU at 4.77 MHz clock speed. Memory : * 16 KB for monitor EPROM upgradable to 64 KB * 16 KB RAM expandable to 64 KB * Battery backup provision for RAM up to 64 KB. Keyboard & Display : * 16 x 2 Alpha numeric LCD Display. * 101 Keys IBM Compatible Keyboard. Timer, Parallel I/O, Coprocessor, Interrupt and Bus Expansion: * 48 TTL I/O lines brought out to two nos of 26 pin FRC Connector. * 1 Number of standard RS232C compatible serial port brought out to a 9 pin D type male connector. * One RS232 Cable provided. * 3 Channel 16 bit counter/timer using 8253 terminated in a 10 pin connector (One Channel Used for baud rate generation.) * Fully buffered address data and control signals terminated at a 50 pin header (VXTBUS) for interfacing VBMB Series of experiment boards and bus expansion. * 8 Nos. of Interrupts using 825 Special Features : * Kit Operates with a single +5V/D.C supply * The Kit and the Power Supply are mounted on a attractive light Gray Color fiber glass cabinet with fiber glass top cover Software * Built-in line assembler and disassembler * Powerful debugging monitor to develop user program. Documentation Support : (2 Manuals) * MICRO 86/88 Technical Reference Manual * User/Student's work Book. Built-in SMPS Power Supply * Input :230 V A.C - Output:+5 V/3.5 A,+12 V/150 mA	2
---	------	--	---

4	8051	8051 MICROCONTROLLER TRAINER KIT Processor : * 89C51 Microcontroller, 12MHz Clock speed Memory : * Program Memory RAM-32KB * Data Memory RAM-32KB * Program Memory EPROM-32KB Peripherals Keyboard and Display * 16 x 2 LCD Display * IBM PC Keyboard is provided and also reset and interrupt keys are provided (RREKey) Parallel I/O Bus Expansion * One no. of 8255 connections are terminated in one 26-pin FRC header (24 I/O lines) * One VXT-Bus (50 pin FRC connector) for interfacing VBMB series of experiment board and bus expansion * Microcontroller port lines are terminated with one 40-pin FRC header Digital I/O * On board 8-digital inputs can be given through 8-Way dip switch * On board 8-digit outputs can be visible through SMD LEDs * The port lines PI used as input (switch) or output LED (selectable hardware) Special Features : * Software single stepping of user programming by instruction for software debugging (at same time user interrupt is not access) * Housed in a sleek plastic cabinet. Serial Port : * On chip serial port will be terminated in 9 pin D Male connector. Built in Power Supply (Multi output) SMPS: * Input: 230 V AC * Output: +5V/3A, +12V/0.5A Battery Backup: * 1 No. of 3V lithium battery/3.6V 4 NICD Battery Documentation support(2 Manuals): * Micro-51 LC User manual	2
---	------	---	---

5	ADC	8 CHANNEL ADC INTERFACE BOARD : *Incorporates ADC 0809 *Start of Conversion by manual switch or software *End of Conversion (EOC) monitored through *Interrupt / Polling *Display of digital data using LED's *All the 8 channel analog inputs terminated at *Screw type connector. *Trimpot is provided on-board to channel 0 or 3 or 6 *Provision for test points & fault analysis points *50 Core Cable *All Address, data and control lines are terminated in a 50 Pin FRC OEN make male connector to interface with VXT bus Note: demonstration if necessary	2
6	DAC	2 CHANNEL DAC INTERFACE BOARD * Two numbers of DAC 0800 * Analog Output: +5V to -5V * DAC outputs are terminated at a suitable connector available on-board * Provision for test points & fault analysis points. * All Address, data and control lines are terminated in a 50 Pin FRC OEN make male Connector to interface with VXT bus. *50 Core Cable Note: demonstration if necessary	2
7	Relay Control System	Relay Control System - a)Electronic Relay using high speed ICs - b)Dead Zone variable from 0-600 mv - c)Hysteresis variable from 0-500mv - d)Built in signal Sources-Sine and square waves of amplitude 0-1v(min) - e)Variable Frequency-0-1 khz - f)IC regulated internal power supplies literature and patch cords included.	1


8	Compensation design and experimental determination of frequency response of lead/lag networks	Compensation design and experimental determination of frequency response of lead/lag networks a) Peak percent overshoot M variable from 20% to 50% b) Steady state P error variable from 50% to 0.5% c) Compensation network implementation through built in variable gain amplifier d) Adjustable gain e) Built in square and sine wave generators for transient and frequency response studies Frequency adjustable from 25 hz- 800hz(approx)	1
---	---	---	---

Measurment Lab

Sl.no	Materials	Specification	Quantity
1	Voltmeter	(0-250)V MI	5 no
2	Ammeter	(0-2)A MI	2 no
3	Ammeter	(0-2)A MC	5 no
4	Rheostat	50 Ω , 5A 250 Ω , 1.6A	5 no
5	DC source	(0-300)V, 3A	3 no
6	Watt meter	500V/250/150, 30A UPF	2 no
7	Clip on meter(analog)	Up to 30 A	3 no
8	Multimeter(analog)	(Unfused 20A max 10 sec each 15 min Fused 2 00Ma MAX 500V DC/AC RMS Protection in resistance range 1000v DC, 750 AC MAX)	1 no
9	Decade resistance Box	(6 Nobx1 ohm, 10ohm, 100 ohm, 1k, 10k, 100k)	1 no
10	Loading rheostat	Three phase 5.1 KW, 440V, 50Hz load per step/Phase	1 no

Electrcal Machines Lab

Sl.No	Particulars	Specification	Quantity(Nos)
1	Ammeter MC	250 mA mA	2
2	Ammeter MC	2A	2
3	Ammeter MC	15A	2
4	Ammeter MC	20A	4
5	Ammeter MI	250 mA	2
6	Ammeter MI	2A	2
7	Ammeter MI	15A	2
8	Ammeter MI	20A	4
9	Voltmeter MC	2V	2
10	Voltmeter MC	20V	1
11	Voltmeter MC	30V	1
12	Voltmeter MC	50V	2
13	Voltmeter MC	150V	2
14	Voltmeter MC	250V	2
15	Voltmeter MC	500V	1
16	Voltmeter MI	20V	1
17	Voltmeter MI	30V	1
18	Voltmeter MI	50V	2
19	Voltmeter MI	150V	2
20	Voltmeter MI	250V	4
21	Voltmeter MI	500V	2
22	Wattmeter UPF	125/250/500V,15/30A	1
23	Wattmeter UPF	62.5/125/250V,5/10A	3
24	Wattmeter UPF	250/500V,15A	2
25	Wattmeter UPF	62.5/125/250V,1/5A	2
26	Rheostat	15 Ω ,2A	2
27	Rheostat	250 Ω ,2A	2
28	Rheostat	500 Ω ,2A	2
29	Rheostat	750 Ω ,1.5A	1
30	Rheostat	350 Ω ,5A	2
31	Loading Rheostat	1 phase 5Kw,250V	2
32	Loading Rheostat	3 phase 5.1Kw,500V	2
33	2 Point starter	For 220V.5HP,DC motor	2
34	3 Point starter	For 220V.5HP DC motor	3
35	Auto transformer	230/0-270V,8A,1 ϕ	2
36	Auto transformer	230/0-270V,20A,1 ϕ	2
37	Mechanical Loading system for motors with spring balance and accessories.	For 5 HP motor	3


 Principal
 Calicut University
 Institute of Engineering
 Thenhipalam, P.O., Malappuram District